


Socket connector cable SIM-M8-3GD-2,5-PU

For sensors and proximity switches.



Socket plugs SEA, SIE and SIM are used for connecting proximity sensors, inductive and optoelectronic sensors, pressure and vacuum switches, and pressure sensors.

- Plug socket SIE
 - Sensor plug SEA
 - Plug socket with cable SIM
 - To 300 V DC
 - To 250 V AC
 - Clip-on or screw-in plug sockets with M8/M12 locknut
 - Cable sheath made from non-polluting polyurethane (-PU)
 - 2.5, 5 or 10 m cable lengths
 - 3, 4 or 5-pin variants
 - Plug sockets with or without integrated LED for standby and function displays
 - Plug socket in welding field resistant design
 - Clean Design plug socket with cable, with detent (-CDN)
- These cables have BGA/FDA approval for use in the food processing industry.

Plug socket SIE
Plug SEA

These plugs and plug sockets are configured by the user. They are available in 3, 4 and 5-pin variants with M8 or M12 locknut. An insert with an LED for displaying the operating status is available for plug socket SIE-GD. With plug type SEA-3GS-M8-S, the cable is clamped using a screw terminal.

Plug sockets with cable SIM-K
These clip-on sockets with cable do not have locknuts for attaching the plug socket to the sensor. Available with straight socket GD or angled socket WD.

Plug socket with cable SIM-M8/SIM-M12
Depending upon the variant, these plug sockets have an M8 or an M12 locknut for secure mounting. The plug sockets are available in 3-pin or 4-pin variants. Plug sockets PSL and NSL for PNP and NPN switching outputs have encapsulated electronics.



Catalogue page

Part no.: 159420

Page:2

Type SIM-M12-RS has a PVC cable with steel sheath. It is thus suitable for use in welding equipment.

SIM-M8-3GD-2,5-PU

Socket connector cable

Data sheet

Part no.: 159420

Page:1

Feature	Data/description
Ambient temperature min. standard	-40 °C
Ambient temperature max. standard	70 °C
Correlation ambient temperature /hours	Fixed cable installation
Ambient temperature max. screwed-in	-5 °C
Ambient temperature max. limited	70 °C
Ambient temperature class, screwed in	Flexible cable installation
Air connection type elec.	Cable/socket
Number of cores	3
Core cross section	0,25 mm²
Length of cable	2500 mm
Diameter of connecting cable	4,5 mm
Material, cable sheath	TPE-U(PU)
Degree of protection	IP67