

PT 나사의 표준 규격 치수표

규격	나사산				기준경			
	나사산수 (25.4m/m에 대하여)	피치 (P)	산의 높이 (h)	등급 (r - r ¹)	수나사			표준길이 (나사끝에서)
					외경(d)	유효경(d ²)	골지름(d ¹)	
					암사나			
외경(D)	유효경(D ²)	골지름(D ¹)						
PT 1/8"	28	0.9071	0.581	0.12	9.728	9.147	8.566	3.97
PT 1/4"	19	1.3368	0.856	1.18	13.157	12.301	11.445	6.01
PT 3/8"	19	-	-	-	16.662	15.806	14.950	6.35
PT 1/2"	14	1.8143	1.162	0.25	20.955	19.793	18.631	8.16
PT 3/4"	14	-	-	-	26.441	25.279	24.117	9.53
PT 1"	11	2.3091	1.479	0.32	33.249	31.770	30.291	10.39
PT 1 ¼"	11	2.3091	1.479	0.32	41.910	40.431	38.952	12.70
PT 1 ½"	11	-	-	-	46.324	44.845	42.803	12.70
PT 2"	11	-	-	-	59.614	58.135	56.656	15.88
PT 2 ½"	11	2.3091	1.479	0.32	75.184	73.705	72.226	17.46
PT 3"	11	-	-	-	87.884	86.405	84.926	20.64
PT 3 ½"	11	-	-	-	100.330	98.851	97.372	22.23
PT 4"	11	2.3091	1.479	0.32	113.030	111.551	110.072	25.40
PT 5"	11	-	-	-	138.430	136.951	135.472	28.58
PT 6"	11	-	-	-	163.830	165.351	160.872	28.58
PT 7"	11	2.3091	1.479	0.32	189.230	187.751	186.272	34.93
PT 8"	11	-	-	-	214.630	213.151	211.672	38.10
PT 9"	11	-	-	-	240.030	238.551	237.072	38.10
PT 10"	11	2.3091	1.479	0.32	265.430	263.951	262.472	41.28
PT 12"	11	-	-	-	316.230	314.751	313.272	41.28